

Models

V-3000+
V-4000
V-5000
V-7000
V-8000
V-9000

Description

Dynatech V Series power Amplifiers deliver from 500Watts to 7200 Watts of power in two to three rack spaces. High current transistors combined with low noise input amplifiers enable the V series to deliver exceptional power. Built around robust and advanced toroidal transformers, they deliver clean power on demand. The advanced protection circuitry guards against short circuit and open circuit, and also protects against ultrasonic and RF interference. A high current power supply increases reliability and performance. Other features include center-dented gain controls, input peak limiter, and fast recovery to ensure low distortion. The variable speed Fans effectively cool the amp and protect against overheating. Input is through XLR connectors, while you can use Speakon-type or binding post connectors for output. The V Series power amps have sub woofer outputs with a selectable low pass filter at variable frequency upto 200Hz. Dynatech V Power Amplifiers are specially designed for professionals who value high power, audio clarity, reliability and lasting performance.



Specifications

Model	V-9000	V-8000	V-7000	V-5000	V-4000	V-3000+
RMS Output Power (Per Channel, 8Ω)	1600 W	1500 W	1400 W	1000 W	700 W	500 W
RMS Output Power (Per Channel, 4Ω)	2600 W	2500 W	2400 W	1600 W	1200 W	800 W
RMS Output Power (Per Channel, 2Ω)	3600 W	3500 W	3000 W	2100 W	1700 W	1200 W
Rated Power (Bridge 8Ω)	5200 W	5000 W	4800 W	3200 W	2400 W	1700 W
Rated Power (Bridge 4Ω)	7200 W	7000 W	6000 W	4200 W	3200 W	2200 W
Input Sensitivity	0.775V, 1V, 1.4V Selectable					
S/N Ratio (A Weight)	>108 dB					
Frequency Response (+0/-0.25dB)	20Hz - 20 kHz					
Class	H	H	H	H	H	AB
Damping Factor	>1000 : 1	>1000 : 1	>880 : 1	>880 : 1	>700 : 1	>400 : 1
THD (10% Rated Power)	0.05%					
Input Connector	2 XLR					
Input Impedance	20 KΩ Balanced, 10 KΩ unbalanced					
Output Connectors	Speakon + Binding Post					
Cooling	2 × Fan airflow from back to front					
Power Supply	11A@230V AC		230 V AC / 50Hz			
Dimensions (H × W × D)(mm)	133×483×524	133×483×524	133×483×465	132×483×410	132×483×410	88×483×410
Net Weight (1 piece/pack)	32.2 Kgs	32.2 Kgs	32.5 Kgs	29.2 Kgs	25.3 Kgs	17 Kgs
Gross Weight	40 Kgs	39 Kgs	38 Kgs	33 Kgs	32 Kgs	21 Kgs